



Explanations see practical informations on page 6 and 84!

THERMO SAFETY STOREHOUSES

For storing hazardous substances frost-free or at constant temperature

Our standard - double door and lifting attachments for cranes!



- ◆ Mounted delivery (SLT 5 x 4, 5 x 6, 5 x 8, 4 x 6 and 4 x 8 premounted).
- ◆ Safety storehouse insulation: insides of all walls, roof and doors fitted with 60 mm thick, non-flammable insulation material
- ◆ Insulation of base sump tray optional
- ◆ Ground clearance 50 mm by insulated base sump tray
- ◆ Heating according to size and required interior temperature
- ◆ Circumferential splash protection made from sheet steel, except in door area
- ◆ With ground connection to avoid dangerous electrostatic charges
- ◆ **For the storage of flammable liquids a forced ventilation system is required.**



SLT 3 x 2, galvanized, with special fittings



Double door in long side as standard, doors in short side on request!



SLT 6 x 3, galvanized

Model	SLT 1 x 2	SLT 2 x 2	SLT 3 x 2	SLT 4 x 2	SLT 5 x 2	SLT 6 x 2	SLT 4 x 3
External dimensions W x D x H (mm)	2075 x 1075 x 2385	2075 x 2075 x 2385	3075 x 2075 x 2385	4075 x 2075 x 2385	5075 x 2075 x 2385	6075 x 2075 x 2385	4075 x 2875 x 2400
Internal dimensions W x D x H (mm)	1840 x 910 x 1900	1840 x 1840 x 1900	2840 x 1840 x 1900	3840 x 1840 x 1900	4840 x 1840 x 1900	5840 x 1840 x 1900	3840 x 2640 x 1900
Sump capacity (l)	300	660	1000	1000	1300	1500	2 x 1000
Delivery	mounted	mounted	mounted	mounted	mounted	mounted	mounted
Article no., galvanized	H63-1000-A	H63-1001-A	H63-1002-A	H63-1003-A	H63-1004-A	H63-1005-A	H63-1007-C
Article no., galvanized and exterior painted	H63-2000-A	H63-2001-A	H63-2002-A	H63-2003-A	H63-2004-A	H63-2005-A	H63-2007-C
Accessories for model	SLT 1 x 2	SLT 2 x 2	SLT 3 x 2	SLT 4 x 2	SLT 5 x 2	SLT 6 x 2	SLT 4 x 3
Base sump tray insulation	H63-1020-A	H63-1021-A	H63-1022-A	H63-1023-A	H63-1024-A	H63-1025-A	H63-1027-A



THERMO SAFETY STOREHOUSES

Our standard - double door and lifting attachments for cranes!



SLT 5 x 2, galvanized and outside painted, with optional fittings

i For accessories such as forced ventilation, lamps and shelving see page 156/157!



SLT 5 x 6, galvanized and outside special painted

Model	SLT 6 x 3	SLT 5 x 4	SLT 5 x 6	SLT 5 x 8	SLT 4 x 6	SLT 4 x 8
External dimensions W x D x H (mm)	6075 x 2875 x 2385	5075 x 4330 x 2605	5075 x 6560 x 2605	5075 x 8790 x 2605	4075 x 6560 x 2605	4075 x 8790 x 2605
Internal dimensions W x D x H (mm)	5840 x 2640 x 1900	4840 x 4070 x 1900	4840 x 6300 x 1900	4840 x 8530 x 1900	3840 x 6300 x 1900	3840 x 8530 x 1900
Sump capacity (l)	2 x 1400	2 x 1300	3 x 1300	4 x 1300	3 x 1000	4 x 1000
Delivery	mounted	2 components premounted, final installation provided by the customer	3 components premounted, final installation provided by the customer	4 components premounted, final installation provided by the customer	3 components premounted, final installation provided by the customer	4 components premounted, final installation provided by the customer
Article no., galvanized	H63-1009-C	H63-1050-A	H63-1051-A	H63-1052-A	H63-1060-A	H63-1061-A
Article no., galvanized and exterior painted	H63-2009-C	H63-2050-A	H63-2051-A	H63-2052-A	H63-2060-A	H63-2061-A
Accessories for model	SLT 6 x 3	SLT 5 x 4	SLT 5 x 6	SLT 5 x 8	SLT 4 x 6	SLT 4 x 8
Base sump tray insulation	H63-1029-A	H63-1030-A	H63-1031-A	H63-1032-A	H63-1033-A	H63-1034-A