



Explanations see practical informations on page 6 and 84!

SIS TYPE 30 / 600 AS PER DIN EN 14470-1 (TYPE 30)


Approved for the restricted storage of flammable liquids at the workplace as per DIN EN 14470-1 (type 30) and TRGS 510, annex 1

- ◆ Whole construction tested and approved by an authorized materials testing institute as per DIN EN 14470-1 (type 30) with a fire resistance >30 minutes
- ◆ SiS Type 30 / 600 with GS-approved safety (GS-sign)
- ◆ Body made from B1 material RAL 7035 - light grey, door either in RAL 7035 - light grey or RAL 1007 - daffodil yellow
- ◆ Height-adjustable shelves at intervals of 32 mm
- ◆ Automatic thermal closing mechanism if fire occurs
 - Door after temperature increase to $\leq 50^{\circ}\text{C}$ and
 - Inlet and outlet channels after temperature increase to 70°C ($\pm 10^{\circ}\text{C}$)
- ◆ DN 80 ventilation connection for exhaust air extraction on cabinet roof
- ◆ Operation complies with TRGS 510 (approved even without exhaust air connection!)
- ◆ Ground connection in accordance with TRBS 2153 (avoidance of sources of ignition)
- ◆ Markings according to DIN EN 14470-1 / TRGS 510 / ISO 3864 / ASR A1.3
- ◆ SiS Type 30 / 600 with leveling feets for installing cabinet horizontally
- ◆ Door with cylinder lock
- ◆ Door hinged right as standard

With inner fittings:

SiS Type 30 / 600 / SiS Type 30 / 600-1300

- ◆ 1 x base sump tray (sump capacity 22 liters) as per WHG - **Ü-sign according to StawaR**
- ◆ 1 x perforated base tray cover as 1st storing level
- ◆ 3 x shelves (SiS Type 30 / 600-1300: 2 x shelves)
- ◆ **door hold-open device**



SiS Type 30 / 600-1300, Article no. B80-2608-A, door RAL 1007 - daffodil yellow, incl. 2 shelves, base sump tray and perforated cover plate



SiS Type 30 / 600, Article no. B80-2603-A, door RAL 1007 - daffodil yellow, incl. 3 shelves, base sump tray and perforated cover plate



Extraction fans please see page 136!



Socle included, with removable panel

| Model | SiS Type 30 / 600 | SiS Type 30 / 600-1300 |
|------------------------------------|-------------------|------------------------|
| External dimensions W x D x H (mm) | 595 x 595 x 1935 | 595 x 595 x 1315 |
| Internal dimensions W x D x H (mm) | 475 x 515 x 1600 | 475 x 515 x 1108 |
| Door | 1 (DIN right) | 1 (DIN right) |
| Weight (kg) | 147 | 121 |

| Outer body: RAL 7035 - light grey | Material inner fittings | | |
|---|-------------------------|------------|------------|
| Article no., door: RAL 7035 - light grey | sheet steel | B80-2601-A | B80-2607-A |
| Article no., door: RAL 1007 - daffodil yellow | sheet steel | B80-2603-A | B80-2608-A |

| Accessories | Material | Article no. | Article no. |
|-------------|-------------|-------------|-------------|
| Shelf | sheet steel | B80-2611-A | B80-2611-A |